

Enhanced microfluidic mixing via a tricritical spiral vortex instability

S.J. Haward, R.J. Poole, M.A. Alves, P.J. Oliveira, N. Goldenfeld, and A.Q. Shen,

Experimental measurements and numerical simulations are made on fluid flow through cross-slot devices with a range of aspect (depth:width) ratios, $0.4 < \alpha < 3.87$. For low Reynolds numbers Re, the flow is symmetric and a sharp boundary exists between fluid streams entering the cross-slot from opposite directions. Above an α -dependent critical value $20 < \text{Re}_c(\alpha) < 100$, the flow undergoes a symmetry-breaking bifurcation (though remains steady and laminar) and a spiral vortex structure develops about the central axis of the outflow channel. An order parameter characterizing the instability grows according to a sixth-order Landau potential, and shows a progression from second order to first order transitions as α increases. A tricritical point occurs for $\alpha \sim 0.55$. The spiral vortex acts as a mixing region in the flow field and this phenomenon can be used to drive enhanced mixing in microfluidic devices.



- (a) Schematic diagram of a cross-slot device. Fluorescently-dyed fluid enters from positive y and undyed fluid enters from negative y. Flow exits along the x-direction. Confocal microscopy is performed in z-planes, which are scanned through the full depth of the device and used to reconstruct images in the x = 0 plane (green shaded region).
- (b) Three-dimensional (3D) rendering of a vortex structure observed for the flow of water at Re = 75.8 in a cross-slot with α = 1. The image is generated from z-plane images spaced at δz = 5 μ m and has been cropped around the central vortex. The volume shown corresponds to the fluorescently-dyed fluid stream.



Development of the spiral vortex structure in the x = 0 plane as the Reynolds number (Re) is varied: (a) Re = 15.2, (b) Re = 42.8, (c) Re = 60.6, (d) Re = 91.0. Scale bar in (a) represents 200 μ m.